



TECHNICAL DATA SHEET

Article: ***COLORADO***

Thickness: 1.2-1.4 mm

Origin: Bovine

Type of tanning: Mineral, based on Chromium salt

Type of finishing: Semi Aniline

Appearance: Semiglossy, tumbled and embossed

<i>PHYSICAL / MECHANICAL PROPERTIES</i>		
Characteristic	Test Method	Value
Tensile Strength	UNI EN ISO 3376	≥ 10 N/mm ²
Percentage Extension	UNI EN ISO 3376	> 20%
Tear Load	UNI EN ISO 3377-2	≥ 60 N
Distension and strength of surface (Ball burst method)	UNI EN ISO 3379	≥ 7,0 mm
Dry Adhesion of finishing	UNI EN ISO 11644	≥ 2 N/10 mm
Dry Flex Resistance	UNI EN ISO 5402-1	50000 cycles: No damages
Wet Flex Resistance	UNI EN ISO 5402-1	10000 cycles: No damages
<i>COLOUR FASTNESS TESTS</i>		
Characteristic	Test Method	Value
Dry Rub Fastness	UNI EN ISO 11640	100 cycles ≥ 3 grey scale
Wet Rub Fastness	UNI EN ISO 11640	20 cycles ≥ 3 grey scale