



TECHNICAL DATA SHEET

Article: **GOMMA-FLUO**

Thickness: 1.2-1.4 mm

Origin: Bovine

Type of tanning: Mineral, based on Chromium salt

Type of finishing: PU finishing

Appearance: Matt, smooth with rubber feel

| PHYSICAL / MECHANICAL PROPERTIES | | |
|--|--------------------|---------------------------|
| Characteristic | Test Method | Value |
| Tensile Strength | UNI EN ISO 3376 | ≥ 10 N/mm ² |
| Percentage Extension | UNI EN ISO 3376 | > 20% |
| Tear Load | UNI EN ISO 3377-2 | ≥ 60 N |
| Distension and strength of surface (Ball burst method) | UNI EN ISO 3379 | ≥ 7,0 mm |
| Dry Adhesion of finishing | UNI EN ISO 11644 | ≥ 5 N/10 mm |
| Dry Flex Resistance | UNI EN ISO 5402-1 | 20000 cycles: No damages |
| Wet Flex Resistance | UNI EN ISO 5402-1 | 10000 cycles: No damages |
| COLOUR FASTNESS TESTS | | |
| Characteristic | Test Method | Value |
| Dry Rub Fastness | UNI EN ISO 11640 | 100 cycles ≥ 3 grey scale |
| Wet Rub Fastness | UNI EN ISO 11640 | 50 cycles ≥ 3 grey scale |
| Colour Fastness to PVC Migration (Grain Side) | UNI EN ISO 15701 | ≥ 3 grey scale |