



## TECHNICAL DATA SHEET

Article: **HAMPTON**

Thickness: 1.1 - 1.3 mm

Origin: Bovine

Type of tanning: Mineral, based on Chromium salt

Type of finishing: Semi aniline

Appearance: Semi glossy, smooth, soft

<b>PHYSICAL / MECHANICAL PROPERTIES</b>		
<b>Characteristic</b>	<b>Test Method</b>	<b>Value</b>
Tensile Strength	UNI EN ISO 3376	≥ 10 N/mm <sup>2</sup>
Percentage Extension	UNI EN ISO 3376	≥ 20%
Tear Load	UNI EN ISO 3377-2	≥ 60 N
Distension and strength of surface (Ball burst method)	UNI EN ISO 3379	≥ 7,0 mm
Dry Adhesion of finishing	UNI EN ISO 11644	≥ 2 N/cm
Dry Flex Resistance	UNI EN ISO 5402-1	50000 cycles: No damages
Wet Flex Resistance	UNI EN ISO 5402-1	10000 cycles: No damages
<b>COLOUR FASTNESS TESTS</b>		
<b>Characteristic</b>	<b>Test Method</b>	<b>Value</b>
Dry Rub Fastness	UNI EN ISO 11640	100 cycles ≥ 3 grey scale
Wet Rub Fastness	UNI EN ISO 11640	20 cycles ≥ 3 grey scale
Colour Fastness to PVC Migration (Grain Side)	UNI EN ISO 15701	≥ 3 grey scale