



TECHNICAL DATA SHEET

Article: ***WILD***

Thickness: 1.2 - 1.4 mm

Origin: Bovine

Type of tanning: Mineral, based on Chromium salt

Type of finishing: Semi aniline

Appearance: Semi glossy, embossed

PHYSICAL / MECHANICAL PROPERTIES		
Characteristic	Test Method	Value
Tensile Strength	UNI EN ISO 3376	≥ 10 N/mm ²
Percentage Extension	UNI EN ISO 3376	> 20%
Tear Load	UNI EN ISO 3377-2	≥ 60 N
Distension and strength of surface (Ball burst method)	UNI EN ISO 3379	≥ 7,0 mm
Dry Flex Resistance	UNI EN ISO 5402-1	50000 cycles: No damages
Wet Flex Resistance	UNI EN ISO 5402-1	10000 cycles: No damages
Martindale Abrasion Resistance	UNI EN 13520	3200 dry cycles: No worse than a moderate abrasion
COLOUR FASTNESS TESTS		
Dry Rub Fastness	UNI EN ISO 11640	100 cycles ≥ 3 grey scale
Wet Rub Fastness	UNI EN ISO 11640	20 cycles ≥ 3 grey scale
Colour Fastness to PVC Migration (Grain Side)	UNI EN ISO 15701	≥ 3 grey scale